

Heavy duty materials house a simple to use interface, giving you control that's built to last.





Control Panel

Simple to set times and operate with no complicated menus to navigate through.

• Heavy Duty Control Unit

Weather proof and suitable for outdoor installations with display cover to screen.

Automatic Self-Cleaning Cells

The microprocessor automatically reverses the polarity of the electrolytic plates to maximise the self- cleaning process.

Patented Clear Vertical Cell

The clear high strength vertical cell incorporates flow detection and by its design, provides 100% hydrogen gas evolution protection.

Automatic Output Limiting

This protects the power supply from over-salting and allows salt to be added without switching the chlorinator off.

Automatic Low & High Salt Warning

If salt levels fall outside the optimum range, the diagnostic display scrolls an alert.

Automatic Pump Protection

If the pump is starved of water, the chlorinator switches the pump off to prevent damage occurring. Timing can be adjusted for different conditions and pump types.

Automatic Pump Flush

This prevents high chlorine levels corroding pipe work, heat exchangers or in-floor cleaning systems.

Compatible with all Mineral Salt Additives

Pool Lab chlorinators will operate with all mineral salt additives.

Smart diagnostic display

With the touch of a couple of buttons view the volts and amps data on both cell polarities.

Enter history to see cell running hours or chlorine output per day and week.

PL Classic Chlorinator Selection Chart:

MODEL	SALT LEVEL @25degC (PARTS PER MILLION)	CHLORINE GAS OUTPUT (GMS PER HOUR)	MAX. POOL SIZE INDOOR (LITRES)	MAX. POOL SIZE OUTDOOR (LITRES)
PL25	3000	25	150,000	90,000
PL35	3000	35	210,000	126,000
PL45	3000	45	265,000	162,000

^{*}Due to ongoing research and development, Poolpower reserves the right to alter specifications without notice.

To explore the full Pool Lab Water Management range, go to

